



CM102AC20

| | | |
|---------------------------------------|--------------------|---|
| Product | | Control Unit |
| Model | | Key Operated |
| Type | | Stay Put Key Removal at all position |
| Label/Position | | (0-I) 60° |
| Contact | | 1NO+1NC |
| Dia | | 22 mm |
| Current | Ie | 4 A (230V AC) |
| Usage Category | | AC 15 |
| Mechanical Life | Min Qty | 500000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 1200 Elec. 1200 |
| Insulation Voltage | Ui | 300V |
| Impulse Withstand Voltage | Uimp | 2.5 kV |
| Dielectric Strength (Body-Contact) | | 2.500V AC |
| Dielectric Strength (Contact-Contact) | | 1.500V AC |
| Isolation Resistance | | 10 MΩ min. (500V DC) |
| Operating Temperature | | -15 / + 65 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP65 |
| Contact Material | | AgNi |
| Cable Section | | 1.5-2.5 mm ² |
| Screw Torque | | 1,5 Nm |
| Short Circuit Breaking Capacity | Ics | 1 kA |
| Production Time | | 31.12.1899 00:00:00 |
| Serial | | CM Series Metal |
| Specifications | | Die cast metal construction for harsh environment, corrosion-resistant chromate plating |
| | | Non-flammable V0 PA6.6 contact blocks |

Various illumination contact blocks availability

Variety of products for all areas of application

IP65 protection from front side

Standards / Certificates IEC 60947-5-1 TS EN 60947-5-1 UL 508 VDE 0660

