

**D100KDY**

<b>Product</b>		Control Unit
<b>Model</b>		Spring
<b>Type</b>		Flush
<b>Contact</b>		1NO
<b>Color</b>		Green
<b>Dia</b>		16 mm
<b>Head Type</b>		Square
<b>Current</b>	<b>I<sub>e</sub></b>	1,5 A (240V AC)
<b>Usage Category</b>		AC 15
<b>Mechanical Life</b>	<b>Min Qty</b>	500000
<b>Electrical Life</b>	<b>Min Qty</b>	100000
<b>Operating Frequency</b>	<b>On-Off/Hour</b>	Mech. 3000 Elec. 1200
<b>Insulation Voltage</b>	<b>U<sub>i</sub></b>	250V
<b>Impulse Withstand Voltage</b>	<b>U<sub>imp</sub></b>	2.5 kV
<b>Dielectric Strength (Body-Contact)</b>		2.500V AC
<b>Dielectric Strength (Contact-Contact)</b>		1.500V AC
<b>Isolation Resistance</b>		10 MΩ min. (500V DC)
<b>Operating Temperature</b>		-15 / + 80 °C
<b>Pollution Degree</b>		3
<b>Protection Degree</b>		IP50
<b>Contact Material</b>		AgNi
<b>Cable Section</b>		Terminal 2,8x0,5
<b>Short Circuit Breaking Capacity</b>	<b>I<sub>cs</sub></b>	1 kA
<b>Production Time</b>		31.12.1899 00:00:00
<b>Serial</b>		D Series Plastic
<b>Specifications</b>		Non-flammable V0 PA6.6 contact blocks
		Various illumination contact blocks availability
		Variety of products for all areas of application

Ease of use in limited spaces

Standards / Certificates

IEC 60947-5-1 TS EN 60947-5-1 UL 508 VDE 0660

