L2K13MEM124		
Product		Limit Switch
Contact		1NO+1NC
Actuator		Adjustable Roller Arm
Actuator Dia		18 mm
Current	**Ie**	3 A (240V AC)
Usage Category		AC15
Mechanical Life	**Min Qty**	10000000
Electrical Life	**Min Qty**	1000000
Operating Frequency	**On-Off/Hour**	Mech. 3000 Elec. 1800
Insulation Voltage	**Ui**	300 V
Impulse Withstand Voltage	**Uimp**	2.5 kV
Dielectric Strength (Body-Contact)		1.890V AC
Dielectric Strength (Contact-Contact)		1.890V AC
Isolation Resistance		10 MΩ (500 V DC)
Operating Temperature		-25 / + 80 °C
Pollution Degree		3
Protection Degree		IP65
Contact Material		AgNi
Cable Section		1-2.5 mm2
Screw Torque		1.5Nm
Short Circuit Breaking Capacity	**Ics**	1 kA
Production Time		31.12.1899 00:00:00
Serial		L2 Metal Body
Contact Action		Snap Action
Actuator Material		Metal
Specifications	Metal Body and Plastic Cover	
	3 side PG13,5 holes	

	Various actuator options with wide sensitive contact block alternatives for all kind of applications
Standards / Certificates	TS EN 60947-5-1 UL 508 VDE 0660